



**Durable 60A Pin & Sleeve assemblies** provide reliable power for your next **live event, motion picture, or theatrical application.**

- Assembled with **60A 4/5 Type SOOW cable** and IEC 60309 listed Hubbell plug and connector
- **4" clear heat shrink** on both ends
- Solid **one-piece pin construction** for reliable electrical contact
- **Gasketed sealing ring** provides watertight seal
- **Heavy-duty external cord grips**
- **IEC 60309 Pin and Sleeve Watertight** for outdoor use
- **Waterproof seals** to resist harsh weather and rough working conditions

### PIN & SLEEVE EXTENSIONS

Cable	Description	Length	Weight (lbs.)	Part Number
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	5'	11.9	P045B005HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	10'	18.5	P045B010HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	15'	25.1	P045B015HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	25'	38.3	P045B025HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	40'	58.1	P045B040HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	50'	71.3	P045B050HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	75'	104.3	P045B075HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	100'	137.3	P045B100HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	125'	170.3	P045B125HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	150'	203.3	P045B150HBL560PC
4/5 Type SOOW	560 P&C – Hubbell (560P9W/560C9W)	200'	269.3	P045B200HBL560PC