



Assembled with UL and c(UL) Listed SC cable made from annealed no. 30 gauge bare copper stranding

- Banded every 24" with heavy-duty glued shrink
- Durable CPE insulation
- Meets/exceeds flame test requirements of UL and c(UL)
- Resistant to sunlight, water, ozone, abrasion, acids, heat, flame, and chemicals
- Excellent flexibility and durability

## OPTIONS

- Custom lengths
- Custom cable identification
- All standard cam-lock colors:  
Black, White, Brown, Yellow, Red, Orange, Green, and Blue

## TIE-IN SETS

RATING	MALE END	FEMALE END	CABLE	PART NUMBER
400A, 600VAC	Bare	(5) 16 Series Cams (Black, White, Red, Blue, Green)	4/0 SC	S40BXXXFB
200A, 600VAC	Bare	(5) 16 Series Cams (Black, White, Red, Blue, Green)	2/0 SC	S20BXXXFB
100A, 600VAC	Bare	(5) 16 Series Cams (Black, White, Red, Blue, Green)	#2 SC	S02BXXXFB

NOTE: Reverse ground or reverse ground/neutral available.

## PIGTAILS

RATING	MALE END	FEMALE END	CABLE	PART NUMBER
400A, 600VAC	16 Series Cams	Bare	4/0 SC	S40BXXXMB
400A, 600VAC	Bare	16 Series Cams	4/0 SC	S40BXXXFB
200A, 600VAC	16 Series Cams	Bare	2/0 SC	S20BXXXMB
200A, 600VAC	Bare	16 Series Cams	2/0 SC	S20BXXXFB
100A, 600VAC	16 Series Cams	Bare	#2 SC	S02BXXXMB
100A, 600VAC	Bare	16 Series Cams	#2 SC	S02BXXXFB

NOTE: Pigtails available with bare end, lug, or pin.